



**INDUSTRIAL
ADHESIVES**
of Indiana

**8202 Indy Lane
Indianapolis, IN 46214**

Product Data RM 001

An Acrylic emulsion for bonding Melamine, Vinyl, HPL, PVC Banding, Metal, Stone, Tile, Acrylics, Wood Veneers. Produces a clear dry. For face to edge joints, apply adhesive to porous surface first then mate the surfaces. Clamp, staple, screw, joint and hold for at least one hour depending on ambient temperature. Clean with water when wet, denatured alcohol when dry.

Viscosity	5000 cps
Solids	45%
pH	9.0 - 10
Freeze thaw stable	No
Color	White (wet) Clear Dry
Polymer type	Vinyl Acrylic
Packaging	One gallons, 5 Gallon Pail, 20 Gallon Drum. Larger sizes on request.

The information on this Product/Technical Data sheet reflects the latest information and characteristics concerning this product. Seller makes no other warranty or representation of any kind, express or implied concerning this product including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. NO WARRANTIES SHALL BE IMPLIED BY LAW AND NO AGENT OF SELLER IS AUTHORIZED TO ALTER THIS WARRANTY IN ANY WAY.

The exclusive remedy against seller shall be a claim for damages not to exceed the purpose price of the product, without regard to whether such a claim is based on breach of warranty or tort.